

Système sans fil HD 2.4GHZ avec écran fractionnable 7"



D16044 : Kit caméra sans fil HD

Discover the D16044 camera kit, our latest-generation wireless system. Designed to meet the demands of professionals, this kit offers exceptional performance:

- HD 1080P camera
- 300 m transmissions distance!
- 130° camera angle
- Easy installation
- Automatic pairing
- Multi-mode split screen

TECHNICAL CHARACTERISTICS



LCD 7" color multi-display monitor

- High resolution display 1024 x 3 (RGB) x 600
- 4 cameras expandable
- Recording via micro SD card (not supplied)
- Automatic pairing with a unique code
- 12 / 24 Volts
- Time delay : 200 ms
- 4 languages available: French, English, German, Chinese
- Picture image adjustable for horizontal, vertical, mirror, normal viewing
- System PAL/NTSC
- Reverse distance grid
- Use between -20°C and +70°C

Monitor: D16055

Recording time:

Micro SD MODE	16G	32G	64G	128G
SINGLE	≈ 15h	≈ 30h	≈ 60h	≈ 120h
QUAD	≈ 17h	≈ 34h	≈ 68h	≈ 136h
SPLIT	≈ 18h	≈ 36h	≈ 72h	≈ 144h



CMOS HD 1080P wireless camera

- 12 / 24 Volts
- Waterproof camera (IP69K)
- Micro integrated
- Night vision: 10 m (4 infrared leds)
- Max distance with monitor : 300 m
- Vision angle: 130°
- Use between -20°C and +70°C

Camera: D16045

Antenna spare part: D14326



Option Antenna 7m cable: D14063

Option 1080P wireless magnetic ann re-chargeable camera : D16046



P/N. D16033



SAFETY

Strengths

- HD 720P screen
- HD camera
- IP 69K camera
- Large viewing angle

2 YEARS WARRANTY

1 x HD 720P 7" COLOUR SCREEN

- 7" Digital screen
- Image 16:9
- Resolution 1024 x RGB x 600 pixels
- Max brightness: 300 cd / m2
- NTSC / PAL Auto Switch System
- OSD Menu + remote control
- 3 cameras output
- Built-in speaker
- 12/24V
- Removable sun visor

Equipment supplied in the kit: 1 HD 7" Screen, 1 U-shaped support, 1 remote control



HD COLOR CAMERA x 1

- Sensor: SONY CMOS 1/3
- Resolution: 1280 x 720 (1 million pixels)
- Min illumination: 0,1 Lux (LED lighting)
- Watertight: IP 69K
- Vision angle : 150°
- Tension: 12V
- Mirror image
- Shock resistance: 4G
- Operation temperatures: -20°C to +70°C

Equipment supplied in the kit: 1 HD color camera

Additional camera: P/N. D16043



20 M CABLE x 1- 4 PINS (male/female) screw-on

Equipment supplied in the kit: 1 x 20m cable

Additional cable: 10m cable : P/N. D13621 or 20m cable : P/N. D13622

