



MultiLine Universal Tail Lift Kit

Everything you need in one installation kit

The kit contains everything you need for installation: instructions, schematics, injectors, pre-loomed tubing, connectors and adapters.

Installation time for the pump is about one hour with 15 minutes additional time per lubrication point.

See how easy it is!



Easy-to-install automatic lubrication: your own mechanic can install the Groeneveld MultiLine Tail Lift Kit when and where you want!

Automatic lubrication applies grease in small doses at regular intervals evenly over the surface of the tail lift.

A regularly-refreshed grease film helps keeps out dirt, dust and water.

Advantages of automatic vs. manual lubrication:

- Save time
- Prolong service life
- Reduce repairs and lower maintenance costs
- Improve vehicle uptime
- Cut grease consumption by up to 50%
- Protect your investment and resale value

GROENEVELD LUBRICATION SOLUTIONS




- Improve uptime
- Cut grease consumption
- Protect your investment

Self-install automatic lubrication kit for tail lifts

Universal Tail Lift Kit

Part number	AC724
Reservoir sizes	2.0L
Lubrication points	19
Output per stroke	0.025 cc
Voltage	24V
Maximum working pressure	120 bar (12 MPa)
Maximum operation temperature	60 °C (140 °F)
Minimum operation temperature	-23 °C (-10 °F) with Greenlube NLGI-0-grease. -13 °C (9 °F) with Greenlube NLGI-2 grease

* based on maximum lubricant distribution line length of 10m / 32ft.
Caution: Temperatures with use of non-Groeneveld greases cannot be guaranteed.



Grease options

	Universal grease	Low-temperature grease
Description	Greenlube EP-2	Greenlube LT-00
Classification		
NLGI grade ASTM D217	2	00
DIN 51502	KP2K-20	KP00G-35
ISO 6743	ISO-L-XBCEB2	ISO-L-XCBIB00
Temperature range	-20 to +130°C	-35 to +100°C
Drum sizes	18 & 50 kg	18 & 50 kg

Universal Tail Lift Kit & related parts

Kit no.	Kit description
AC724	Universal Tail Lift Kit (24V, 19 points, grease)
Part no.	Spare part description
AC2522-1	AC2522-1 replacement pump (24V, 24 outlet)
Part no.	Lubricant description
F210058	GV Greenlube EP-2 grease NLGI grade 2 – 18Kg steel pail
F210060	GV Greenlube EP-2 grease NLGI grade 2 – 50Kg steel drum
F210054	GV Greenlube LT-00 grease NLGI grade 00 – 18kg steel pail (low-temperature)
F210057	GV Greenlube LT-00 grease NLGI grade 00 – 50kg steel drum (low-temperature)
Part no.	Accessories description
F104562	Tube cutter
F178054	Manual hand-operated filler pump kit for 18kg steel pail – NLGI-00
F121623	Manual hand-operated filler pump kit for 18kg steel pail – NLGI-2

More details can be found in the instruction manual

