



New-generation lubricants that meet **MAN Truck** specifications

Shell's new-generation lubricants have been developed to meet the demands of modern heavy-duty vehicles and the specific requirements of OEM engineering technology.

Our products deliver durability and efficiency throughout the engine's life cycle, helping to balance the demands of operating conditions, environmental regulations, and maintenance budgets. The process begins with selecting the right lubricant for your vehicle and its needs.

Shell Rimula R7 Plus AM 5W-20

Shell Rimula R7 Plus AM 5W 20 features a low HTHS (high-temperature high-shear) viscosity of 2.6 mPa·s to provide less resistance to flow, meaning less power and fuel are needed to maintain performance in harsh conditions.



Fuel economy

Fulfils the latest MAN M 3977 specification for enhanced fuel economy.



Maintenance savings

Meets the long oil-drain interval (ODI) requirements of the latest Euro VI engines, enabling operators to optimise maintenance schedules and control maintenance costs.



Emissions system compatibility

An advanced low-ash formulation helps to protect exhaust after-treatment devices. This helps keep vehicles emissions-regulation compliant and maintains engine fuel efficiency.



Low wear, low deposits

Additive technology to keep pistons clean, which is essential for long engine life.

A low-SAPS oil with advanced additive technology that helps:

- **enhance** fuel economy and lower emissions
- **reduce** engine friction and extend maintenance intervals.



Shell Rimula range of engine oils specifications

Product	ACEA	API	MAN	Scania	Daimler Truck	Volvo Truck	Renault Truck	Iveco	DAF
Shell Rimula R7 Plus AM 5W-20			M3977						
Shell Rimula Ultra 5W-30	E6, E7, E8, E9, E11	CJ-4	M3477 ¹ , M3677	LDF-4	DTRF 15C110		RLD-3	18-1804 TLS E6 ¹	PSQL 2.1 E LD
Shell Rimula R6 LME Plus 5W-30	E6, E7, E8, E9, E11	CK-4	M3477 ¹ , M3677	LDF-4	DTRF 15C110, 15C120	VDS-4.5	RLD-3	18-1804 TLS E6	PSQL 2.1 E LD
Shell Rimula R6 LM 10W-40	E6, E7, E8, E9, E11	CK-4	M3477 ¹ , M3271-1 ¹		DTRF 15C110	VDS-4.5	RLD-3	NG2 ¹	E6 ¹
Shell Rimula R6 ME E4 5W-30	E4	CF	M3277	LDF-3	DTRF 15B120	VDS-3	RLD-2	TFE ¹	
Shell Rimula R6 M 10W-40	E4, E7	CI-4	M3277, M3377		DTRF 15B120	VDS-3	RLD-2	T3 E4 ¹	

Shell coolant range

Specification – MAN 324 Type NF

Shell Coolant Extra Ready to Use

Specification – MAN 324 Type Si-OAT

Shell Coolant Longlife Plus Ready to Use

Shell range for other applications

Specification – MAN 284Li-H2

Application - Grease (fifth wheel)

Shell Gadus Fifth Wheel Grease

Specification – MAN 283Li-P2

Application - Grease points

Shell Gadus S3 V220C 2

Specification – DIN 51524-3 HVLP 15

Application - Cab tilt system

Shell Tellus S2 VX 15

Shell range of gear and axle oils

Specification – MAN 339 Type L1, Type Z2

Application – Power steering, tipper system, transmission (automatic), retarder

Shell Spirax S6 ATF VM Plus

Specification – MAN 339 Type Z1; Dexron IID

Application – Power steering, tipper system

Shell Spirax S2 ATF AX

Specification – MAN 339 Type Z3²; Dexron III

Application – Transmission (automatic), power steering, retarder, tipper system

Shell Spirax S5 ATF X

Specification – MAN 339 Type Z4

Application – Transmission (automatic, semi-automatic, manual)

Shell Spirax S6 ATF ZM

Specification – MAN 341 GA1, MAN 342 Type S1

Application – Axle, differential, transfer box

Shell Spirax S6 ADME 75W-90

Specification – MAN 341 GA2, 341 GB

Application – Transmission (manual, semi-automatic)

Shell Spirax S6 GTME 75W-80

Specification – MAN 341 Type E4²

Application – Axle, differential

Shell Spirax S6 GXME Ultra 75W-80

Specification – MAN 341 Type Z4, Z5²; ZF TE-ML 02L, 02E², 02H²

Application – Transmission (automatic, semi-automatic, manual), power take-off, transfer box

Shell Spirax S6 GXME 75W-80

Specification – MAN 342 Type M1, M2

Application – Axle

Shell Spirax S3 AX 80W-90

Specification – MAN 342 Type M2, MAN 341 GA1, E2, Z2; ZF TE-ML 02B

Application – Axle, differential, Transmission (Manual, Semi-automatic)

Shell Spirax S3 AM 80W-90

Specification – MAN 342 Type M3

Application – Axle

Shell Spirax S3 AD 80W-90

Specification – MAN 342 Type S1, Type S2²

Application – Axle, differential, transfer box

Shell Spirax S6 AXME 75W-90

¹ meeting requirements of

² suitable for use, follow manual for ODI

Expert lubrication services

Because selecting the right lubrication is such an important decision, we've combined human expertise with technological innovation to make sure you have the right tools, services and insights to get it right.

Shell Lube**Match**

Find the right oil for your vehicle's specific make and model

Shell Lube**Analyst**

Oil condition monitoring that helps prevent potential technical failures

Shell Lube**Advisor**

Technical expertise, on-site, online or over the phone

